

UV紫外線試驗機 UV Climate Resistant Aging Test Chamber

氣候環境試驗設備
Climate Environmental Test Equipment



產品用途：

類比陽光對材料及產品造成的危害試驗，廣泛用於對材料耐氣候性的評價。

Application:

It simulated sunlight damage on The material and product test, is widely used in the evaluation of material climate resistant.

技術參數 Technical Parameters:

型號 Model		UV-350
內部尺寸 (mm) Internal Dimension WxHxD (mm)		1150×550×550
外形尺寸 (mm) External Dimension WxHxD (mm)		1350×1550×600
適用標準 Applicable Standard		GB/T16422 , GB/T5170.9
溫度範圍 Temperature Range		(室溫+15°C)~+70°C , (R.T.+15°C)~+70°C
溫度波動度 Temperature Fluctuation		±0.5°C
濕度範圍 Humidity Range		≥95%R.H.
使用環境溫度 Environmental Temperature for Use		室溫RT±5°C
試驗光源 Test Light Source		UVA , UVB 紫外线燈 UVA , UVB UV light
試驗光源波長 Wave Length of Test Light Source		280~420nm
樣品與燈管中心距 Center Distance between Sample and Tube		50±2mm
燈管與燈管中心距離 Center Distance between Tubes		75±2mm
工作室材料 Material of Internal Case		高級拉絲不銹鋼 Stainless steel with sanding polish
外殼材料 Material of External Case		高級拉絲不銹鋼或烤漆 Stainless steel with sanding polish or painting coated
加熱加濕器 Heating the Humidifier		電熱式蒸汽發生器並加濕
安全系統 Safety System	操作介面 Operation Interface	數位智慧式輕觸鍵輸入 (可程式控制) Digital smart touch key input (programmable)
	運行方式 Running Mode	程式控制 / 恒定式運行 Program / constant running type
	輸入 Input	黑板溫度計 , PT-100感測器 Black panel thermometer , PT-100 Sensor
標準配件 Standard Configuration		不銹鋼樣品架1個 1 pcs Stainless steel shelf
安全配置 Safety Configuration		漏電、超載斷電保護、超溫保護、缺水、觸地保護 Protection of electric leakage,power outage when over-load,over-temperature protection, water short storage,touch the ground protection
電源 Power		AC220V ; 1φ 3線 ; 50/60HZ AC220V ; 1φ 3 lines ; 50/60HZ